

THE ARM PILLOWS ARE INCLUDED IN THE COST.



4AR/S	4AR/S	0E2/3	4P7	0CD	060
760mm 29.92" 1120mm 44.09"	760mm 29.92" 950mm 37.40" 1120mm 44.09"	760mm 29.92" 950mm 37.40" 1120mm 44.09"	760mm 29.92" 810mm 31.89" 1120mm 44.09"	760mm 29.92" 810mm 31.89" 1120mm 44.09"	760mm 29.92" 1120mm 44.09"
4AP/Q	502	4QH	450	440	
760mm 29.92" 1050mm 41.34"   1120mm 44.09"	470mm   18.50"   820mm   32.28"   680mm   26.77"	760mm 29.92" 1060mm 41.73" 1120mm 44.09"		760mm 29.92" 1900mm 74.80" 1120mm 44.09"	760mm 29.92" 2100mm 82.68" 1120mm 44.09"
4AR+4RS	4AP+4RQ	4A	R+4P7+4AS	4AR+0C	D+060+0CD+4AS
1120mi 44.09"			44.0		113.39"
1900mr 74.80"	m	2100mm 82.68"	2710 106.		2880mm 113.39"

## **Technical Information**

## **ADDITIONAL DIMENSIONS:**

Seat Height(cm)47Seat Depth(cm)61Arm Height(cm)72Arm Width(cm)23Leg height(cm)15

## CONSTRUCTION

Covering: Leather/Fabric

Constructured with a combination of Plywood and LVL for enhanced strength and

Frame Composition: durability

Frame Joint Construction: Reinforced using corner blocks, staples, and adhesive.

Suspension System: Coiled Springs

Seat Type: Attached seat cushion

Seat Cushion Composition: Foam

Back Type: Attached back cushion

Back Cushion Composition: Foam
Legs Material: Wood
Legs available colors: Espresso

Reclining Function: Yes.

Features: PWR Reclining, PWR headrest, Zero-Gravity Mech

Wall away distance(cm): 6

**DELIVERY INFORMATION** 

What type of assembly is required NO

**ADDITIONAL DETAILS** 

Recommended Weight Capacity per Seat(kgs): 110 kgs per static seat; 150 per power seat