4157







3Q7	3Q7	36A/B	3M2/3
1020mm 40.16"	1020mm 40.16"	1020mm 40.16"	1020mm 40.16"
1020mm 40.16"	1120mm 44.09"	855mm 33.66"	1160mm 45.67"
	1020mm 40.16"	1020mm 40.16"	1020mm 40.16"
		···	

## **Technical Information**

**ADDITIONAL DIMENSIONS:** 

Seat Height(cm)49Seat Depth(cm)57Arm Height(cm)60.5Arm Width(cm)29

**CONSTRUCTION** 

Covering: Leather

Constructured with a combination of Plywood and LVL for enhanced strength and

Frame Composition: durability

Frame Joint Construction: Reinforced using corner blocks, staples, and adhesive.

Suspension System: Sinuous Springs

Seat Type: Attached Seat cushion

Seat Cushion Composition: Foam

Back Type: Attached Back cushion

Back Cushion Composition: Foam

Reclining Function: Yes

Features: PWR Reclining, PWR Headrest

Wall Clearance Needed To Recline(cm): 16

**DELIVERY INFORMATION** 

What type of assembly is required Back

**ADDITIONAL DETAILS** 

Recommended Weight Capacity per Seat(kgs): 110kgs per static seat; 150 per power seat